# Safety Data Sheet

**Date of Issue** 11 January 2016

**Version** 1.01

## 1. Product and Company Identification

**Product Name** TORCH F/X™

**Supplier/Manufacturer**
STEEL F/X®
893 E FACTORY DR
ST. GEORGE, UT 84790

**Emergency Telephone #'s**
**(800)-710-1273 (U.S.)**
**(800)-710-1273 (Canada)**

**Technical Phone #** **(800)-710-1273**

**HMIS Hazard Rating:**

4 = Severe
3 = Serious
2 = Moderate
1 = Slight
0 = Minimal

## 2. Hazards Identification

**Emergency Overview**

**WARNING! Corrosive!**
CAUSES EYE AND SKIN IRRITATION. MAY BE HARMFUL IF INHALED OR SWALLOWED. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.
Do Not Get in Eyes or on Skin or Clothing. Use Only With Adequate Ventilation. Keep Container Tightly Closed and Sealed Until Ready for Use. Wash Thoroughly After Handling.

**Potential Acute Health Effects**

**Inhalation:** May be Harmful if Inhaled.

**Ingestion:** May be Harmful if Swallowed

**Skin:** Severely Irritating to the Skin.

**Eyes:** Severely Irritating to Eyes. Risk of Serious Damage to Eyes.

**Over-Exposure Signs/ Symptoms:**

**Inhalation:** Irritation, Sore Throat

**Ingestion:** No specific data.

**Skin:** Adverse Symptoms May Include The Following:
Irritation
Redness

**Eyes:** Adverse symptoms may include the following:
Pain or Irritation
Watering
Redness

**Medical Conditions Aggravated by Over-Exposure:** Pre-Existing Disorders Involving Any Target Organs Mentioned in This (M)SDS as being at Risk May Potentially be Aggravated by Over-Exposure to This Product.

**This Material Safety Data Sheet Has Been Prepared in Accordance with OSHA (U.S.) Standards & Canada's Workplace Hazardous Materials Information System (WHMIS). See Toxicological Information (Section 11)**

PROPRIETARY FORMULA-TRADE SECRET

## 3. Composition/Information on Ingredients

| Name/Identifier | CAS Number | % (v/v) | Synonyms |
|---|---|---|---|
| Selenious Acid | 7446-08-4 | .01-.03% | Selenium, Selenous Acid |
| Sulfuric Acid | 7664-93-9 | .01 - 05% | Dihydrogen Sulfate, Oil of Vitriol |
| Distilled Water | 7732-18-5 | 98-99.8% | $H_2O$, De-Ionized Water, Water Distillate |

There Are No Additional Ingredients Present Which, Within the Current Knowledge of the Manufacturer and/or Supplier and in the Concentrations Applicable, Are Classified as Hazardous to Health or the Environment and Hence Require Reporting in This Section.

## 4. First Aid Measures

If Ingestion, Irritation, or Any Type of Over-Exposure or Symptoms of Over-Exposure Occur During or Persists After use of This Product, Contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN Immediately; Have Material Safety Data Sheet Information Available. Never Give Anything By Mouth to an Unconscious or Convulsing person.

**Eye Contact:** Check for and Remove Any Contact Lenses. Immediately Flush Eyes With Running Water For at Least 15 Minutes, Keeping Eyelids Open. Seek Immediate Medical Attention.

**Skin Contact:** Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use Solvents or Thinners.

**Inhalation:** Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

**Ingestion:** If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

**Notes to Physician:** No Specific Treatment. Treat Symptomatically. Contact Poison Treatment Specialist Immediately if Large Quantities Have Been Ingested or Inhaled.

## 5. Firefighting Measures

**Flammability of the Product** N/A

**Extinguishing Media** Use an extinguishing agent suitable for the surrounding fire.
Use water only! Do NOT use carbon dioxide or dry chemical. (Dry Ferric Nitrate Only)

**Unsuitable Methods** None known.

**Special Exposure Hazards** Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Hazardous Combustion Content** Decomposition products may include the following materials: None Known

**Special Protective Equipment for Firefighters** Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## 6. Accidental Release Measures

**Personal Precautions** No action shall be taken involving any personal risk or without suitable training.

Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

**Environmental Precautions** Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform Relevant Authorities if the product has caused environmental pollution in the items mentioned above. Copper Sulfate is Toxic to Aquatic Life.

## 6. Accidental Release Measures (Continued From Page 2)

**Large Spill**

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

**Small Spill**

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## 7. Handling and Storage

**Handling** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Do not swallow. Do not get in eyes or on skin or clothing. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Vapors are heavier than air and may spread along floors. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Storage** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Do not store above the following temperature: 120F / 49C.

## 8. Exposure Controls/Personal Protection

| Name | | Result | ACGIH | Ontario | Mexico | Mfg. |
|---|---|---|---|---|---|---|
| Selenious Acid (Dry) | TLV | Not Established | 5 mg/m³ | 10 mg/m³ | N/E | N/E |

**Key To Abbreviations**

- **A** = Acceptable Maximum Peak
- **ACGIH** = American Conference of Governmental Industrial Hygienists.
- **C** = Ceiling Limit
- **F** = Fume/s
- **IPEL** = Internal Permissible Exposure Limit
- **R** = Respirable
- **S** = Potential Skin Absorption
- **SR** = Respiratory Sensitization
- **SS** = Skin Sensitization
- **STEL** = Short Term Exposure Limit Values
- **TD** = Total dust
- **TLV** = Threshold Limit Value
- **TWA** = Time Weighted Average
- **N/E** = Not Established

**Consult Local Authorities for Acceptable Exposure Limits.**

**Recommended Monitoring Procedures**

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**Engineering Measures**

**Hygiene Measures**

Good General Ventilation Should be Sufficient to Control Worker Exposure to any Airborne Contaminants.
Wash Hands, Forearms and Face Thoroughly After Handling Chemical Products, Before Eating, Smoking & Using the Lavatory, and at the End of the Working Period.

## 8. Exposure Controls/Personal Protection (Cont. From Page 3)

**Eyes** : Chemical Splash Goggles.

**Hands** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Gloves** : Nitrile, Latex, Rubber or Neoprene

**Respiratory** : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Personal protective equipment for the body should be

**Skin** : selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Environmental Exposure Controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## 9. Physical and Chemical Properties

**Physical State** : Liquid.

**Flash Point** : No Flash Point.

**Color** : Faint Purple

**Odor** : None.

**pH** : ± 2

**Boiling/Condensation Point** : >100°C (>210°F)

**Melting/Freezing point** : Freeze Point: <32ºF 1.01

**Specific Gravity** : (Water is 1.0)

**Density (lbs. / gal.)** : 8.47

**Vapor Pressure** : Not Available.

**Vapor Density** : Similar to Water.

**Volatility** : 0% (w/w)

**Evaporation Rate** : Not Available.

**Solubility** : Soluble in Water.

**Partition Coefficient: N-Octanol/Water** : Not Available.

**% Solid. (w/w)** : <0.04%

## 10. Stability and Reactivity

**Stability** : Stable Under Recommended Storage and Handling Conditions (See Section 7).

**Conditions to Avoid** : No Specific Data.

**Materials to Avoid** : Reactive or Incompatible With the Following Materials: Oxidizing Materials, Strong Alkalis (Bases)

**Hazardous Decomposition Products** : Under Normal Conditions of Storage and Use, Hazardous Decomposition Products Should Not Be Produced.

**Hazardous Polymerization** : Under Normal Conditions of Storage and Use, Hazardous Polymerization Will Not Occur.

# 11 . Toxicological Information

**Acute Toxicity**

| Product/Ingredient Name | Result | Species | Dose | Exposure |
|---|---|---|---|---|
| Selenious Acid<br>Distilled Water | LD50 Oral<br>N/A | Rat | 900mg/kg (Rat) | - |

**Conclusion/Summary :** (Ferric Nitrate Dust): CARCINOGENIC EFFECTS(Ferric Nitrate Dust: Not available. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. The substance is toxic to lungs, mucous membranes. Repeated or prolonged exposure to the substance can produce target organs damage. Repeated exposure of the eyes to a low level of dust can produce eye irritation. Repeated skin exposure can produce local skin destruction, or dermatitis. Repeated inhalation of dust can produce varying degree of respiratory irritation or lung damage.

**Chronic Toxicity Conclusion/Summary**

**Target Organs** : Contains Material Which May Cause Damage to the Following Organs: Kidneys, Upper Respiratory Tract, Skin, Eyes, Stomach.

# 12 . Ecological information

**Environmental Effects** : None Known

# 13 . Disposal considerations

**Waste Disposal**

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**Disposal Should be in Accordance With Applicable Regional, National and Local Laws and Regulations.**

**Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for Additional Handling Information and Protection of Employees. Section 6. Accidental Release Measures.**

# 14. Transport Information

| | TDG | Mexico | IMDG |
|---|---|---|---|
| **UN Number** | Not regulated. | Not regulated. | Not regulated. |
| **UN Proper Shipping Name** | - | - | - |
| **Transport Hazard Class(es)** | - | - | - |
| **Packing Group** | - | - | - |
| **Environmental Hazards**<br>**Marine Pollutant Substances** | No.<br>Not Applicable. | No.<br>Not Applicable. | No.<br>Not Applicable. |

**Additional Information**

## 14. Transport Information

**TDG** : None Identified.
**Mexico** :None-Identified.
**IMDG** UN#3260 Class:8 PG:II EMS-No:F-A
Proper Shipping Name: Corrosive Solid, Acidic, Inorganic.NIC, N.O.S. (Ferric nitrate nonahydrate)

**Special Precautions For User :** **Transport Within User's Premises:** Always Transport in Closed Containers That are Upright and Secure. Ensure That Persons Transporting the Product Know What To Do in the Event of an Accidental Spill or Leakage.

## 15 . Regulatory Information

**United States inventory (TSCA 8b)** : All components are listed or exempted.
**Australia inventory (AICS)** : All components are listed or exempted.
**Canada inventory ( DSL )** : All components are listed or exempted.
**China inventory (IECSC)** : All components are listed or exempted.
**Europe inventory ( REACH )** : Please contact your supplier for information on the inventory status of this material.
**Japan inventory (ENCS)** : All components are listed or exempted.
**Korea inventory (KECI)** : All components are listed or exempted.
**New Zealand ( NZIoC )** : All components are listed or exempted.
**Philippines inventory (PICCS)** : All components are listed or exempted.

**Canada**

**WHMIS (Canada)** : Class E: Corrosive Liquid.

**Mexico Classification**

**Flammability** : 0 **Health** : 2 **Reactivity** : 0

## 16 . Other Information

**Hazardous Material Information System (U.S.A.)**

**Health** : 2 **Flammability** : 0 **Physical hazards** : 2
**( * ) - Chronic Effects**

**CAUTION: HMIS® Ratings are Based on a 0-4 Rating Scale, With 0 Representing Minimal Hazards or Risks, and 4 Representing Significant Hazards or Risks. Although HMIS® Ratings Are Not Required on SDS's Under 29 CFR 1910. 1200, The Preparer May Choose to Provide Them. HMIS® Ratings Are to be Used With a Fully Implemented HMIS® program. HMIS® is a Registered Mark of the National Paint & Coatings Association (NPCA).**

**The Customer is Responsible For Determining the PPE Code For This Material.**

**N.F.P.A. (National Fire Protection Association) U.S.A.**

**Health** : 2 **Flammability** : 0 **Instability** : 0

**Date of previous issue** : 06/25/2011
**SDS Preparer** : WWIH

**Indicates information that has changed from previously issued version.**

**Disclaimer**

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by STEEL F/X®, and to recommend precautionary measures for the storage and handling of the products.*
*No Warranty or Guarantee is Given in Respect of the Properties of the Products. No Liability Can Be Accepted For Any Failure To Observe The Precautionary Measures Described In This Safety Data Sheet (SDS), Or For Any Misuse Of The Products.*